MAP D2, LOT 13-6
SITE PLAN


# ADMINISTRATION BUILDING

TOWN OF MILFORD RECEIVED

JAN 22 2024

DB ZBA\_\_\_Office\_\_\_\_

594 ELM STREET
MILFORD, NEW HAMPSHIRE



#### PREPARED FOR/RECORD OWNER

### III HITCHINER MANUFACTURING CO., INC.

594 ELM STREET
MILFORD, NEW HAMPSHIRE 03055
(603) 673-1100
www.hitchiner.com

18 JANUARY 2024

REVIEW ONLY


INDEX OF PLANS		
SHEET No.	TITLE	
1 OF 16	MASTER SITE PLAN	1"= 50'
2 OF 16	NOTES AND LEGENDS	
3 OF 16	EXISTING CONDITIONS PLAN	1"= 20'
4 OF 16	SITE DEMOLITION PLAN	1"=20'
5 OF 16	SITE PLAN - PHASE 1	1"=20'
6 OF 16	SITE PLAN - PHASE 2	1"=20'
7 OF 16	EROSION CONTROL PLAN - PHASE I	1"=20'
8 OF 16	EROSION CONTROL PLAN - PHASE II	1"= 20'
9 OF 16	UTILITY PROFILES	1"= 20' H 1"= 4' V
10-12 OF 16	DETAIL SHEET - GENERAL SITE	
13 OF 16	DETAIL SHEET - EROSION CONTROL	
14 OF 16	LANDSCAPE PLAN	1"= 20'
15 OF 16	DETAIL SHEET - LANDSCAPE	
16 OF 16	PHOTOMETRIC SITE LIGHTING PLAN	1"= 20'




Civil Engineers/Land Surveyors
3 Congress Street 131 Middlesex Turnpike
Nashua, NH 03062 Burlington, MA 01803
(603) 883-2057 (781) 203-1501

www.hayner-swanson.com







#### **SURVEY NOTES:**

- THE EXISTING TOPOGRAPHY, AS SHOWN ON THE PLANS, IS BASED ON AN ACTUAL FIELD SURVEY MADE ON THE GROUND IN SEPTEMBER 2010 THEU FEBRUARY 2022 AND IS IN ACCORDANCE WITH THE TOWN OF MILFORD, NEW HAMPSHIRE SITE PLAN REGULATIONS.
- IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY THE ACCURACY OF THE EXISTING TOPOGRAPHY PRIOR TO BARTHWORK OPERATIONS. NO CLAIM FOR EXTRA WORK DUE TO TOPOGRAPHIC INACCURACY SHALL BE CONSIDERED AFTER EARTHWORK HAS COMMERCED.
- NGVD29 DATUM HAS BEEN USED FOR THIS PROJECT.
- THE CONTRACTOR SHALL ONLY USE BENCHMARKS AS PROVIDED BY THE ENGINEER.
- UTILITY SERVICE LOCATIONS AS SHOWN ON THIS PLAN ARE APPROXIMATE AND SHALL BE VERIFIED PRIOR TO ANY CONSTRUCTION

#### **TOWN OF MILFORD** CONTACTS

#### PLANNING DEPARTMENT MILFORD PLANNING BOA TOWN HALL - ONE UNION MILFORD, NH 03055

ATT: TERREY DOLAN (603) 249-0620

#### ENGINEERING DEPARTMENT MILFORD DEPT. OF PUBLIC WORKS / ENGINEERING 289 SOUTH STREET MILFORD, NH 03055

ATT: RICK RIENDEAU, DIRECTOR (603) 673-1562

#### FIRE DEPARTMENT

CODE ENFORCEMENT OFFICE: ONE UNION SQUARE MILFORD, NH 03055

ATT: TIM HERLIHY, BUILDING INSPECTOR (603) 249-0520

#### UTILITY COMPANY

CONTACTS

1. WATER/SEWER MILFORD WATER UTILITIES AND WASTE WATER TREATMENT FACILITY 584 NASHUA STREET MILFORD, NH 03055

ATT: DAVID BOUCHER, SUPT. (603) 249-0660

DIRO IAUOITAN

#### 3. TELEPHONE: CONSOLIDATED COMMUNICATIONS, CONSOLIDATED CONSO

#### SITE DEMOLITION NOTES:

- THE CONTRACTOR IS RESPONSIBLE FOR THE DEMOLITION, REMOVAL, AND DISPOSING IN A LOCATION APPROVED BY ALL GOVERNING AUTHORITIES, OF ALL STRUCTURES, PLON, WALLS, FLUX, FOUNDATIONS, PARKING, DRIVES, DRAINAGE, STRUCTURES, UTILITIES, ETC., SUCH THAT THE MAPROVEMENTS SHOWN ON THE REMAINING PLAIS CAN BE CONSTRUCTED. ALL FACULIES TO BE REMOVED SHALL BE UNDERCUT TO SUITABLE MATERIAL AND BROUGHT TO GRADE WITH SUITABLE COMPACTED FILL MATERIAL PRET INTE CONTRACTED FILL MATERIAL PRET INTE CONTRACTED FILE OF THE PROPERTY OF THE PROPERTY
- THE CONTRACTOR IS RESPONSIBLE FOR REMOVING ALL DEBRIS FROM THE SITE AND DISPOSING THE DEBRIS IN A LAWFUL MAINER. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL PERMITS REQUIRED FOR DEMOLITION AND DISPOSAL.
- THE CONTRACTOR SHALL COORDINATE WITH RESPECTIVE UTILITY COMPANIES PRIOR TO THE REMOVAL AMOUNT RELOCATION OF UTILITIES. THE CONTRACTOR SHALL COORDINATE WITH THE UTILITY COMPANY AMOUNT RELOCATION OF UTILITIES. THE CONTRACTOR SHALL COORDINATE WHITH THE UTILITY COMPANY FOR THE UTILITY COMPANY FOR THE UTILITY COMPANY FOR THEIR SERVICES. THE CONTRACTOR THE SERVICES THE CONTRACTOR THE COMPANY FOR THE PROPRIET OF THE P
- THE LOCATIONS OF ALL EXISTING UTILITIES SHOWN ON THIS PLAN HAVE BEEN DETERMINED FROM THE BEST INFORMATION AVAILABLE AND ARE GOVEN FOR THE CONTRACTOR. THE BEST INFORMATION AVAILABLE AND ARE GOVEN FOR THEM ACCURACY, PRIOR TO THE START OF ANY DEMOLITION ACTIVITY, THE CONTRACTOR SHALL NOTIFY THE UTILITY COMPANIES FOR ON SITE LOCATIONS OF EXISTING UTILITIES.
- ALL EXISTING SEWERS, PIPING AND UTILITIES SHOWN ARE NOT TO BE INTERPRETED AS THE EXACT LOCATION, OR AS THE OILY OBSTACLES THAT MAY OCCUR ON THE SITE. VERIFY EXISTING CONDITIONS AND PROCEED WITH CAUTION AROUND ANY AUTO-PATED FEATURES. GIVE NOTICE TO ALL UTILITY COMPANIES REGARDING DESTRUCTION AND REMOVAL OF ALL SERVICE LINES AND CAP ALL LINES BEFORE PROCEDURG WITH THE WORK.
- BEFORE FROLEDING WITH THE WORK.

  ELECTRICAL, TELEPHONE, CABLE, WATER, FIBERGLASS PIPE (HEAT), FIBER OPTIC CABLE AND/OR GAS
  LINES INEDING TO BE REMOVED OR RELOCATED SHALL BE COORDINATED WITH THE AFFECTED UTILITY
  COMPANY, ADEQUATE THIS SHALL BE PROVIDED FOR RELOCATION AND GLOSE COORDINATION WITH THE
  UTILITY COMPANY IS RECESSARY TO PROVIDE A SMOOTH TRANSITION IN UTILITY SERVICE. CONTRACTIOR
  SHALL PAY CLOSE ATTENTION TO EXISTING UTILITIES WITHIN THE ANY ROAD RIGHT OF YIAY DURING
  CONSTRUCTION.
- CONTINUOUS ACCESS SHALL BE MAINTAINED FOR THE SURROUNDING PROPERTIES AT ALL TIMES DURING DEMOLITION OF THE EXISTING FACILITIES

#### **CONSTRUCTION NOTES:**

- ALL WORK SHALL CONFORM TO THE APPLICABLE REGULATIONS AND STANDARDS OF THE TOWN OF MILEORD, AND SHALL BE BUILT IN A WORKMANLIKE MANNER IN A COCROANICE WITH THE FLANS AND SPECIFICATIONS. THIS STANDARD SPECIFICATIONS FOR ROAD AND BROISE CONSTRUCTION, STATE OF NEW HAMPSHIRE, DEPARTMENT OF FUBIC WORKS AND HIGHWAYS, APPROVED AND ADOPTED, LATEST EDITION, ARE HERBER INCCEPORATED BY REFERENCE.
- RODA BIOLD RANGE CONSTRUCTION SHALL CONFORM TO THE TYPICAL SECTIONS AND DETAILS SHOWN ON THE PLANS, AND SHALL MEET THE REQUIREMENTS AND SHOCK FOR RODA CONSTRUCTION, BOARD OF PUBLIC VARVES, MICROS HEW HAVE A STANDARD SHECK, CANCAR FOR SEVERS AND DEVAILS DAVID OF PUBLIC VARVES, MICROS HEW HE AND THE SHALL SHOWN OF PUBLIC VARVES, MICROS HEW HE AND THE SHALL SHOWN OF THE SHALL SH
- NOTED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING AND DETERMINING THE LOCATION, SIZE AND ELEVATION OF ALL EMBINING UTILITIES, SHOWN OR INTO BENOM ON THESE PLAIRS, PRIOR TO THE STRAT OF ANY CONSTRUCTION. THE EMBINING SHOWN OF THE STRAT OF ANY CONSTRUCTION. THE CONTRACTOR WAS ANY OF THE STRATE OF PROCEEDING WITH THE YORK. THE CONTRACTOR SHALL BE RESPONSIBLE FOR CONTACTING 'DIG SAFE' AT 1483-341-273 AT LEAST Z HOURS BEFORE DOGING.
- ALL TRAFFIC CONTROL SIGNS SHALL BE IN ACCORDANCE WITH THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES, LATEST EDITION.
- SEWER SHALL BE CONSTRUCTED IN ACCORDANCE WITH PLANS AND SPECIF.CATIONS AND WITH THE REQUIREMENTS OF THE DEPARTMENT OF ENVIRONMENTAL SERVICES, WE A POC. AND ANY STROTER REQUIREMENTS OF THE WATER AND SEVEN COMMISSION, WATER UTILITIES STRAIGHT OF THE WATER AND SEVEN AND CONSTRUCTION OF WATER AND SEVEN INFARSTRUCTURE. A TEST EDITION.
- ALL WATER LINE, MYDRAHT VALVES AND APPURTENANCES SHALL BE INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF THE WATER AND SEVER COMMISSION, WATER UTILITIES, STANDARS REQUIREMENTS OF THE WATER AND SEVER HAD CONSTRUCTION OF WATER AND SEVER INFRASTRUCTURE, LATEST EDITION.
- ALL STUMPS SHALL BE DISPOSED OF OFF-SITE IN A LEGAL MANNER.

#### **CONSTRUCTION SEQUENCE:**

- CLEAR SITE ACCORDING TO PLAN
- CONSTRUCTION OF TEMPORARY SEDIMENT AND EROSION CONTROL MEASURES, TO BE IN ACCORDANCE WITH THE PLANS. PERIMETER CONTROLS TO BE INSTALLED PRIOR TO EARTH MOVING OPERATIONS.
- GRUB SITE ACCORDING TO PLAN.
- CUT AND DISPOSE OF ANY DEBRIS PRODUCED DURING THE CLEARING AND GRUBBING ACTIVITY.
- CONSTRUCT DETENTION BASINS AND SWALES PRIOR TO ROUGH GRADING IN EACH PHASE. SEED AND MULCH IMMEDIATELY.
- SITE GRADING OF BUILDING AND PARKING AREAS. ALL CUT AND FILL SLOPES SHALL BE SEEDED AND MULCHED AFTER BEING CONSTRUCTED.
- INSTALLATION OF UNDERGROUND UTILITIES AND CATCH BASINS SHALL BE PROTECTED FROM SEDWIENT IN ACCORDANCE WITH THE "SILTBACK DETAIL". THE CONTROL SHALL REMAIN WITH THE STIE IS SUFFICIENTLY STRAILED BY IRRAP SHALL BE PLACED AT EACH HADAWAL DUTLET.
- AS THE BUILDING IS COMPLETED, ALL DISTURBED AREAS SHALL BE PERMANENTLY STABILIZED.
- NO PORTION OF THE PROJECT SHALL BE LEFT DISTURBED AND UNSTABILIZED FOR A PERIOD OF 45 DAYS OR GREATER. ALL DISTURBED AREAS SHALL BE PERMANENTLY STABILIZED PRIOR TO WHITER CONDITIONS. STABILIZATION GHALL BE DEFINED AS 70% LECETATIVE GROWTH BY NOVEMBER 1ST OR INSTALLATION OF EROSION CONTROL MATTHIX.
- COMPLETED AREAS SHALL BE STABILIZED 72 HOURS AFTER COMPLETION.
- ALL PERMANENT STORM WATER MANAGEMENT MEASURES SHALL HAVE A HEALTHY STAND OF VEGETATION ESTABLISHED PRIOR TO DIRECTING RUNOFF INTO THEM
- FINAL PAVING OF PARKING LOT.
- LOAM AND SEED ALL DISTURBED AREAS
- INSPECTION OF ALL SEDIMENT AND EROSION CONTROL MEASURES.
- SITE LANDSCAPING ALONG WITH PERMANENT SEEDING OF ALL DISTURBED AREAS.
- REMOVE ANY TEMPORARY EROSION CONTROL MEASURES NOT NEEDED

#### **GENERAL NOTES:**

- ALL CONTRACTORS AND SUBCONTRACTORS INVOLVED WITH STORM WATER POLLUTION PREVENTION SHALL OSTAIN A COPY OF THE STORM WATER POLLUTION PREVENTION PLAN AND THE STATE OF NEW HAMPSHIRE NATIONAL POLLUTION SCHARGE ELIMINATION SYSTEM GENERAL PERMIT (IPDES PERMIT) AND BECOME FAMILIAR WITH THEIR CONTENTS.
- THE CONTRACTOR SHALL IMPLEMENT BEST MANAGEMENT PRACTICES AS REQUIRED BY THE SWPPP. ADDITIONAL BEST MANAGEMENT PRACTICES SHALL BE IMPLEMENTED AS DOTATED BY CONDITIONS A' NO ADDITIONAL COST OF OWNER THROUGHOUT ALL PHASES OF CONSTRUCTION.
- LOAM AND MATERIAL STOCKPILE AREAS AS SHOWN ARE APPROXIMATE AND SUBJECT TO CHANGE STOCKPILE AREAS SHALL BE SURROUNDED BY SILT FENCE AND RE-SEEDED IF THEY ARE LEFT UNTOUCHED FOR MORE THAN ITEN (10) DAYS.
- AN AREA SHALL BE CONSIDERED STABLE ONLY IF THE FOLLOWING HAS OCCURRED:
  - BASE COURSE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAVED.

  - A MILINUM OF 85 PERCENT VEGETATED GROWTH HAS BE ESTABLISHED.

     AMILINUM OF 51 NICHES OF NON-EROSIVE MATERIAL SUCH AS STONE OR RIPRAP HAS BEEN INSTALLED.
  - OR, EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED.

#### ► UTILITY QUALITY LEGEND 4

SUBSURFACE UTILITIES AS DEPICTED ON THIS PLANARE IDENTIFIED BY QUALITY LEVELS DEFINED BY CIASCE 33-02 "ASCE STANDARD GUIDEUNE FOR COLLECTION AND DEPICTION CENTRING USBSURFACE UTILITY DATA."

LEVEL A (a) PRECISE HORIZONITAL AND VERTICAL LOCATION OF UTILITIES OBTAINED BY ACTUAL EXPOSURE AND SUBSEQUENT MEASUREMENTS OF SUBSURFACE UTILITIES.

LEVEL B (a) INFORMATION OBTAINED THROUGH THE APPLICATION OF APPROPRIATE SURFACE GEOPHYSICAL METHODS TO DETERMINE THE EXISTENCE AND APPROXIMATE HORIZONTAL POSITION OF SUBSURFACE UTILITIES, (E. DIGSAF LEVEL C (c) INFORMATION OBTAINED BY SURVEYING AND PLOTTING VISIBLE ABOVE-GROUND UTILITY FEATURES AND BY USING PROFESSIONAL JUDGEMENT IN CORRELATING THIS INFORMATION TO QUALITY LEVEL D INFORMATION.

LEVEL D (d) INFORMATION DERIVED FROM EXISTING RECORDS OR ORAL RECOLLECTIONS

#### ▶ UTILITY NOTE ◀

THE UNDERGROWN UTILITIES DEPOTED MERCON HAVE SEEN LOCATED FROM FILLD SURVEY HE PORMATION AND PLOTTED FROM EXISTING WIND HEAD STATE OF THE PROPERTY OF THE SURVEYOR HAS NOT PHYSICALLY LOCATED THE SURVEYOR HAS NOT PHYSICALLY LOCATED THE PROPERTY OF THE PROP

#### ► ZONING NOTE 4

THE ZOUNIOGRALEPING STEDAYS DEPOTED ON THIS PLANARE THOSE WE HAVE INTERPRETED FROM THE LATEST ZOWING ORDINACE OF THE BIRKEPHINY AND, AS SUAN ABE CAXY OPINIOR EXPRESSED BY MAYIRERSWAISOU, INC. THE FIRLA INTERPRETATION OF THE ORDINANCE CAN GOAL YEAR OF THE APPROPRIATE ZOWING AUTHORITY, SINCE BULDING ORBEITATION, PROPOSED USES, AND OTHER FACIORS CAN AFFECT THE STEBACK, PRIOR TO AN OVERLOPMENT OF THIS PROPERTY, THE BUILDERWOWER RUST CONSULT MITH THE TOWNCH'T TO INSIDE THE CORRECT APPLICATION OF THE ZOWING ORBINIANCE.



_	LEGEND		ABBR	EVIATIO	ONS
K&h	EXISTING GROWND CONTOUR	GENER		UTILIT	-
[100]	EXISTING GROUND CONTOUR EXISTING SPOT ELEVATION PROPOSED GRADE PROPOSED GRADE STORM DRAIN & CATCH BASIN STORM DRAIN & CATCH BASIN STORM DRAIN & HEADWALL WATER MAIN & HIVD SETTION SANTARY SEWER & MAIHOLES WATER MAIN & GATE VALVE OAS LINE & GATE VALVE UNLITY POLE WITH GUY SUPPORT STREET LIGHT LIGHT POLES OVERHEAD ELECTRIC & TELEPHONE UNDERGROUND ELECTEL & MAIHOLES SIGIN N.H. HIGHWAY BOUND STONE BOUND CONCRETE BOUND IROUPHN	GENER APPROX BIT EM BWA BYL COND DYL ELEV EXIST FE FF GF MAX MAII 11T.S. PROP SWA SYL TYP	AL  APPROXIMATE BITMINIOUS BASEMENT FLOOR ELEVATOR BROKEH WHITE UNE BROKEH YELLOW LINE CONCRETE DOUBLE YELLOW LINE ELEVATION ELEVATION ELISTING FLOOR ELEVATION ARAGE FLOOR ELEVATION ANAMUM MINIMUM MINIT TO SCALE PERFORATED PROPOSED SOLID WHITE LINE SOLID YELLOW LINE TYPICAL WALKOUT FLOOR ELEVATION	UTILIT CB CJ. CMP CQ. CU DB. GR. DJ. DMH FES HW FM HOPE HYD INV OCS PVC RCM RIM SMH UGE UGT YD	CATCH BAS CAST IRON CORRUGAT CLEANOUT COPPER TY DOUBLE OF DUCTILE IR DRAIN MAN FLARED EN HAD WALL FORCE MA HIGH DETIS HYDRAIN INVERT COUTLET CO UTLET CO UTL
O CGS	IRON PIPE COTTON GIN SPINOLE DRILL HOLE & STOLE WALL		EROSI	ON LEG	END
* TEM 1	DRILL HOLE & STOKE WALL STOKE BOUND TO BE SET IRON PIN TO BE SET TEMPORARY BEINCHMARK BUILDING SETRACK LINE WETLAND FLAGGING LINAT WETLAND BUFFER LINE WARE FENCE CHANLINK FENCE STOCKADE FENCE FOST A RAIL FENCE CURBING VERTICAL GRANTE CURBING STORMWATER RUNOFF DIRECTION HANDICAP PARKING SPACE HANDICAP SIGNAL RUNDP PARKING SPACE LANDICAP SIGNAL RUNDP PARKING SPACE COUNT STREET ADDRESS GUARDRAIL		169   169	EXISTING O PROPOSEL WETLAND I RUNOFF DI SILT SOCK ORANGE C SILT-SACK GRAVEL CO	GROUND CO O GRADE FLAGGING L RECTION ONSTRUCTI INLET PRO DINSTRUCTION FION MATTIN

-@-

00

PAVEMENT SAWCUT

B &A MET-4

D
TP3A TP12

Ø

SEE MUTCD FOR TEXT DIMENSIONS

STOP

E.

VAN ACCESSIBLE

REINFORCED CONCRETE PROPOSED FULL-DEPTH PAVEMENT

PROPOSED PAVEMENT OVERLAY

BORING LOCATION & IDENTIFIER

TEST PIT LOCATION & IDENTIFIER

RETAINING WALL

ROCK/BOULDER

CONFEROUS TREE

DECIDUOUS TREE

DATUM NOTE

SIGN LEGEND

DATUM HAS BEEN USED FOR THIS TO CONVERT TO NAVD88 DATUM, SUBTRACT 0.83 FT

DENTIFICATION SIZE NUMBER WIDTH/HEIGH

TEXT DIMENSIONS

SEE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AN HIGHWAYS

SEE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND

SEE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND HIGHWAYS

30"/30"

12"/18"

18"/9"

R1-1

R7-8

R7-8P

DECORATIVE WALL


DECORATIVE VILWI FELICE

TREE LINE

SHRUBS

20+00 CENTER LINE STATIONING

#### **CURB. SIDEWALK & PAVEMENT** MARKING LEGEND



PAINTED ARROW

CAST IRON PIPE

DUCTILE IRON PIPE

FLARED END SECTION

HIGH DENSITY POLYETHYLENE PIPE

OUTLET COUTROL STRUCTURE

POLYVIAYL CHLORIDE PIPE REINFORCED CONCRETE PIPE

UNDERGROUND TELECOMM YARD DRAIN

DRAIN MANHOLE

CLEANOUT COPPER TYPE K WATER PIPE

EXISTING GROUND CONTOUR PROPOSED GRADE

WETLAND FLAGGING LIMIT

ORANGE CONSTRUCTION FENCE

GRAVEL CONSTRUCTION EXIT

TEMPORARY STONE CHECK DAM

STABILIZATION MATTING

SILT-SACK INLET PROTECTION DEVICES

RIM ELEVATION

SEWER MANHOLE UNDERGROUND ELECTRIC

CORRUGATED METAL PIPE

MARKING LEGEND		
	VERTICAL GRANITE CURB	
	SLOPE GRANITE CURB	
	TIP DOWN CURB & SIDEWALK RAN	
	CONCRETE CURB & SIDEWALK	
4° DYL	DOUBLE YELLOW LINE	
	CROSSWALK	
	PAINTED ISLAND	
بالا	18" STOP BAR	
62222	DETECTABLE WARNING PANELS	


J S E E


COMPANY MANUFACTURING


HITCHINIR I **3** 


BUILDING

MOTES AND LEGEND S (MAP D2. LOT 13-6) ADMINISTRATION ₹




















#### SILTSAK® NOTES:

- 1.0 THE SILTSAKO SHALL BE MAJUFACTURED FROM WOVE!! POLYPROPYLENE AND SEWN BY A DOUBLE I BEEDLE MACHINE, USING A HOHOST STRENGTH INLON THREAD.
  2.0 THE SILTSAKO SEMN SHALL HAVE A CERTIFIED AVERAGE WIDE WIDTH STRENGTH PER ASTM D-4884
- STANDARDS AS FOLLOWS: SILTSAKD STYLE TEST METHOD TEST METHOD
- SILTSANO STYLE


  SILTSANO STYLE

  ASTIM D-4884 ISSO (1850)

  THE GUAR FLOW ASTIM D-4884 ISSO (1850)

  THE SILTSANO WILL BE MANDFACTURED TO FIT THE COPENING OF THE CACHE SING OR DROP INCES. TWO DUMP STRANS THE SILTSANO SHALL HAVE A RESTRAINT CORD APPROXIMATELY NALFANY UP THE SACK TO KEEP THE SILTSANO SHALL HAVE A RESTRAINT CORD APPROXIMATELY NALFANY UP THE SACK TO KEEP THE SICES AWAY FROM THE CACHE ASSIN WALLS, THIS THE SILTSANO SHALL HAVE A RESTRAINT CORD APPROXIMATELY NALFANY UP THE SACK TO KEEP THE SICES AWAY FROM THE CACHE ASSIN WALLS, THIS THE SILTSANO SHALL HAVE A RESTRAINT CORD APPROXIMATELY NALFANY SHEEL REALIST OF REDCATING THE SICES AWAY FROM THE CACHE ASSIN WALLS, THIS THE SILTSANO SHALL HAVE A RESTRAINT CORD APPROXIMATELY NALFAND THE SICES AWAY FROM THE CACHE ASSIN WALLS, THIS THE SILTSANO SHALL HAVE A RESTRAINT CORD APPROXIMATELY NALFAND SHALL HAVE A RESTRAINT CORD APPROXIMATELY NA FROM THE SILTSANO BARD FROM THE SILTS

#### SILTSAK® DETAIL



## FILTER FABRIC

#### SECTION 'A'-'A' VIEW

- . THE EXIT SHALL BE MAINTAINED IN A CONDITION THAT WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHT-OF-WAYS. THIS MAY REQUIRE TOP DRESSING, REPAIR ANOUR CLEAN OUT OF ANY MEASURES USED TO TRAP SEDIMENT.
- WHEN NECESSARY, WHEELS SHALL BE CLEANED PRIOR TO EXITING THE SITE ONTO A PUBLIC RIGHT-OF-WAY.
- WHEN WASHING IS REQUIRED, IT SHALL BE DONE ON AN AREA STABILIZED WITH CRUSHED STONE THAT DRAINS INTO AN APPROVED SEDIMENT TRAP OR SEDIMENT BASIN.
- CONSTRUCTION SPECIFICATIONS AND MAINTENANCE REQUIREMENTS SHOWN IN NHOES STORMWATER MANUAL VOLUME 3.

#### TEMPORARY GRAVEL CONSTRUCTION EXIT

#### ANGULAR 2'-3' CRUSHED STON TOP OF EARTHEN E TRANSITION EXISTING CHANNEL INTO SEDMENT TRAP PLAN 'Δ' ----6" MINIMUM FREEBOARD 6" (CENTER OF RIPRAP 6" LOWER THAN ENDS 12' MIN SECTION A

SECTION B

#### SEDIMENT TRAP INSTALLATION NOTES:

- . SEE PLAN VIEW FOR: LOCATION, LENGTH AND WIDTH OF SEDIMENT TRAP.
- -LOCATION, LENGTH AND WIDH OF SEDMENT TRAP-SEDIMENT TRAPS SHALL BE SIZED TO PROVIDE A VOLUME OF 3,600 FER ACRE OF CONTRIBUTING DRAILAGE AREA. SEDIMENT TRAPS SHALL BE INSTALLED PRIOR TO ANY UPGRADIENT LAND-DISTURBING ACTIVITIES.
- UPGMADERI LARZOUS UNBIRS ACTIVITIES.
  SEDIMENT TRAP BERM SHALL BE CONSTRUCTED FROM
  MATERIAL FROM EXCAVATION. THE BERM SHALL BE
  COMPACTED TO 95% OF THE MAXIMUM DENSITY IN
  ACCORDANCE WITH ASTM D598.
- SEDIMENT TRAP OUTLET TO BE CONSTRUCTED OF WELL-GRADED ANGULAR 2'-3' CRUSHED STONE. THE TOP OF THE EARTHEN BERM SHALL BE A MITBIUM OF 6" HIGHER THAN THE TOP OF THE OUTLET STRUCTURE.
- THE ENDS OF THE OUTLET STRUCTURE SHALL BE A MISSIAUM OF 6' HIGHER THAN THE CENTER OF THE OUTLET STRUCTURE SHALL BE A MISSIAUM.

#### SEDIMENT TRAP MAINTENANCE NOTES:

- I. INSPECT BMPs EACH WORKDAY, AND MAINTAIN THEM IN EFFECTIVE OPERATING CONDITION MAINTENANCE OF BMPs EFFECTIVE OPERATIVS CONDITION I MAINTENANCE OF BRAY-SHOULD BE PROACTIVE, NOT REACTIVE, INSPECT BMPS AS SOON AS POSSIBLE (AND ALVIAYS WITHIN 24 HOURS) FOLLOWING A STORM THAT CAUSES SURFACE EROSION, AND PERFORM NECESSARY MAINTENANCE.
- AND PERFORM NECESSARY MAINTENINCE.
  FREQUETI OSERVATIONS AND MAINTENINCE ARE
  NECESSARY TO MAINTAIN BMPS IN EFFECTIVE OPERATING
  CONDITION INSPECTIONS AND CORRECTIVE MEASURES
  SHOULD BE DOCUMENTED THOROUGHLY
  WHERE BMPS HAVE FAILED. REPAIR OR REPLACEMENT
  SHOULD BE INITIATED UPON DISCOVERY OF THE FAILURE.
- SHOULD BE IMMINIBED ON ON DECOMENT OF THE PROCESS


  REMOVE SEDIMENT ACCUMULATED IN TRAP AS NEEDED TO

  MAINTAIN THE FUNCTIONALITY OF THE BMP. TYPICALLY

  WHEN THE SEDIMENT DEPTH REACHES 1/2 THE HEIGHT OF

  THE OUTLET.
- THE COTTE! SHALL REMAININ PLACE UNTIL THE CONTRIBUTING DISTURBED AREA IS STABILIZED. WHEN SCOMENT TRAPS ARE REMOVED. THE DISTURBED AREA SHALL BE COVERED WITH TOPSOIL, SEEDED AND MULCHED OR OTHERWISE STABILIZED.


#### SEDIMENT TRAP DETAIL



SILT SOCK BARRIER SHALL BE FILTREXX SILTSOXX NATURAL PLUS (OR APPROVED EQUAL) AND SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.

- SILT SOCK BARRIER SHALL BE INSPECTED IMMEDIATELY AFTER EACH RAINFALL AND AT LEAST DAILY DURING PROLONGED RAINFALL. ANY REPAIRS THAT ARE REQUIRED SHALL BE MADE IMMEDIATELY.
- IF THE SILT SOCK SHOULD DECOMPOSE OR BECOME INEFFECTIVE, THE BARRIER SHALL BE REPLACED PROMPTLY.
- SEDMENT DEPOSITS SHOULD BE INSPECTED AFTER EVERY STORM EVENT. THE DEPOSITS SHOULD BE REMOVED WHEN THEY REACH APPROXIMATELY ONE-THIRD THE HEIGHT OF THE BARRIER.
- 5. SEDIMENT DEPOSITS THAT ARE REMOVED OR LEFT IN PLACE AFTER THE BARRIER HAS BEEN REMOVED SHALL BE GRADED TO CONFORM WITH THE EXISTING TOPOGRAPHY AND VEGETATED.

#### SILT SOCK DETAIL



STABILIZATION MATTING BY NORTH AMERICAN GREEN BIONET \$150BN, OR APPROVED EQUAL

- PREPARE SOIL BEFORE INSTALLING BLANKETS, INCLUDING ANY NECESSARY APPLICATION OF LIME, FERTILIZER, AND SEED
- BEGIN AT THE TOP OF THE SLOPE BY A!KHORING THE BLANKET (II A 6" DEEP X 6" WIDE TRENCH WITH APPROXIMATELY 12" OF BLANKET EXTENDED BEYOND THE UP-SLOPE PORTION OF THE TRENCH. APPROXIMATELY 12" OF BURNET EXTENDED BETOND THE UP-STOPPE PORTION OF THE INVESTOR APPROXIMATELY 12" APPRIL THE BOTTOM OF THE TREICH BACKFULL AND COMPACT THE TREICH AFTER STAPLING, APPRI SEED TO COMPACTED SOIL AND FOLD REMAINS 12" PORTION OF BLANGET BACK OVER SEED AND COMPACTED SOIL SECURE BLANKET OVER COMPACTED SOIL WITH A ROY OF STAPLES/STAKES SPACED APPROXIMATELY 12" APPRAT ACROSS THE WITH OF THE BLANKET.
- ROLL THE BLAIMETS (A.) DOWNIOR (B.) HORIZOHTALLY ACROSS THE SLOPE. BLAIKETS WILL LURGOLL
  WITH APPROPRIATE SIDE. AGAINST THE SOIL SURFACE. ALL BLAIKETS MUST BE SECURELY FASTENED
  TO SOIL SURFACE BY PLACING STAPLES/STAKES IN APPROPRIATE LOCATIONS AS PER MANUFACTURES
  RECOMMENDATION.
- S. CONSECUTIVE BLANKETS SPUCED DOWN THE SLOPE MUST BE PLACED END OVER END (SHINGLE STYLE) WITH AN APPROXIMATE 3" OVERLAP. STAPLE THROUGH OVERLAPPED AREA, APPROXIMATELY 12' APART ACROSS ENTIRE BLANKET WIDTH
- 6. PLACE STAPLES/STAKES PER MANUFACTURE RECOMMENDATION FOR THE APPROPRIATE SLOPE BEING

NOTE: IN LOOSE SOIL CONDITIONS, THE USE OF STAPLE OR STAKE LENGTHS GREATER THAN 6" MAY BE NECESSARY TO PROPERLY SECURE THE BLANKETS. STABILIZATION MATTING DETAIL

#### **GENERAL NOTES**

- ALL SOIL EROSION AND SEDMENT CONTROL MEASURES SHALL BE IN ACCORDANCE WITH STANDARDS AND SPECIFICATIONS THEREOF IN NEW HAMPSHIRE DEPARTMENT OF ENVIRONMENTAL SERVICES STORMWATER MAINLAIS, VOLUME 1-3, LATEST EDITION.
- THE WORK AREA SHALL BE GRADED, SHAPED, AND OTHERWISE DRAINED IN SUCH A MAINTER AS TO JUNIOUSE SOL EROSION, SILTATION OF DRAINAGE CHAINIES, DAMAGE TO EXISTING VEGETATION, AND DAMAGE TO PROPERTY OUTSIDE THE LIMITS OF THE WORK AREA. SILT FENCES, STRAW BALES ANDOR DETERMINON BASINS WILL BE INCESSARY TO ACCOMPLISH THIS BUIL.
- STRIPPED TOPSOIL SHALL BE STOCKPILED, WITHOUT COMPACTION, AND STABILIZED AGAINST EROSION IN ACCORDANCE WITH "TEMPORARY STABILIZATION OF DISTURBED AREAS", AS OUTLINED IN NOTE No. 4.
- ACCURAGE THIS TERPOPART OF DEBENDARS:

  FERNORARY STABLIZATION, OF DISTURBED AREAS:

  EEED BED PREPARATION:

  AND AGRICULTURAL LIMESTONE AT A RATE OF SO LBS PER 1,000 SF AND INCORPORATED INTO THE SOIL

  THE SOIL, FERTILIZER AND UNESTONE SHALL BE TILLED TO PREPARE FOR SEEDING.

SPECIES	RATE PER 1,0	00 SF DEPTH	SEEDING DATES
WINTER RY	E 25 LBS	1'	08/15 TO 09/15
OATS	2 5 LBS	1*	04/15 TO 10/15
ANNUAL RY	E GRASS 1.0 LBS	0 25"	08/15 TO 09/15
B. MULCHING CONSERVA	: MULCH SHOULD BE USED O ATION OF MOISTURE WILL FAR	N HIGHLY ERODABLE CILITATE PLANT ESTA	AREAS, AND WHERE BLISHMENT AS FOLLOWS:
TYPE	RATE PER 1,0	00 SF USE &	COMMENTS

MAY BE USED WITH PLANTINGS, MUST BE ANCHORED TO BE USED ALONE USED WITH TREE AND SHRUB WOOD CHIPS OR BARK MULCH MUST BE BIODEGRADABLE. USE IN SLOPE AREAS AND AREAS DIFFICULT TO VEGETATE.

USE IN SPECIFIC AREAS AS SHOWN OF PLAN OR AS NEEDED.

CRUSHED STONE

- PERMANENT STABILIZATION OF DISTURBED AREAS: A. ALL ROADWAYS SHALL BE STABILIZED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE. B ALL CUT AND PILL SLOPES SHALL BE SEEDEDLOAMED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE.
  GRADE.
- THE SMALLEST PRACTICAL AREA SHALL BE DISTURBED DURING CONSTRUCTION, BUT IN NO CASE SHALL EXCEED 5 ACRES AT ANY ONE TIME BEFORE DISTURBED AREAS ARE STABILIZED.
- AN AREA SHALL BE CONSIDERED STABILIZED IF ONE OF THE FOLLOWING HAS OCCURRED:

  A BASE COURSE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAVED.

SPREAD TO GREATER THAN W'THICKNESS

- A ADMINIUM OF 55% VEGETATED GROWTH HAS BEEN ESTABLISHED.
   A MINIMUM OF 3 INCHES OF NON-EROSIVE MATERIAL SUCH AS STOKE OR RIPRAP HAS BEEN INSTALLED.
   OR, EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED.
- ALL AREAS SHALL BE STABILIZED WITHIN 45 DAYS OF INITIAL DISTURBANCE.
- NEW HAMPSHIRE DEPARTMENT OF ALTERATION OF TERRAIN PERMIT No.
- SITE LOCATION: 42° 50' 24° N. LATITUDE, 71° 41' 58° W. LONGITUDE (PER GOOGLE EARTH)
- TOTAL AREA OF DISTURBED SOILS: 98,000± SF
- REFERENCE IS MADE TO THE LATEST EDITION OF THE FEDERAL REGISTER (63 FR 7657), ENVIRONMENTAL PROTECTION AGENCY INPOS GENERAL PERMITS FOR STORMWATER DISCHARGES FROM CONSTRUCTION ACTIVITIES, FOR ADDITIONAL HIFORMATION CONTACT (202) 584-954.05 OR www.eap.gov/inpdes/stormater.
- ACTIVITIES. FOR ADDITIONAL INFORMATION CONTROL (AND SEASON SOCKWARPS SENTINDESSESSION THE EITING CONTINUES OF THE STORMWATER POLLUTION PREVENTION PLAN (SWEPP) SHALL BE RETAILED ON-SITE OF THE DURATION OF THE CONTRACT AND BE MADE AVAILABLE TO LOCAL, STATE AUTOFEDERALICE OCCO EFFORCECEUT PERSONNES.
- THIS PROJECT SHALL BE MANAGED TO MEET THE REQUIREMENTS AND INTENT OF RSA 430.63 AND AGR 3500 RELATIVE TO INVASIVE SPECIES; AND FUGITIVE DUST IS CONTROLLED IN ACCORDANCE WITH ENV-A
- TURF REINFORCEMENT MATS, IF UTILIZED, SHALL BE COVERED WITH SOIL TO PREVENT EXPOSURE OF THE MATS TO THE SURFACE.
- THERE SHALL BE NO PLASTIC, OR MULTI-FILAMENT OR MONOFILAMENT POLYPROPYLENE NETTING OR MESH WITH AN OPENING SIZE OF GREATER THAN 18 INCHES MATERIAL UTILIZED (NOT APPLICABLE TO TURF REINFORCEMENT MATS).

#### **WINTER CONDITION NOTES**

- ALL PROPOSED POST-DEVELOPMENT VEGETATED AREAS WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY COTOBER 15<sup>th</sup>, OR WHICH ARE DISTURBED AFTER OCTOBER 15<sup>th</sup>, SHALLE BE STABILIZED BY SEEDING AND INSTALLING BROSON CONTING BLAKKETS ON SLOPES GREATER THAN 3.1, AND SEEDING AND PLACING 3 TO 4 TOILS OF MULCH PRE ACKE, SECURED WITH ANCHORED HETTING AND ELSEWHERE THE PLACEMENT OF ERRORD CONTING BLANKETS OR MULCH AND INTITING SHALL NO COCCUM OVER ACCUMULATED SHOW OR OF PROZEN GROWID AND SHALL BE COMPLETED IN ADVANCE OF THAN ON SPRING MELT EVENTS.
- ALL DITCHES OR SWALES WHICH DO NOT EXHIBIT A MINIMUM OF 65% VEGETATIVE GROWTH BY OCTOBER 15<sup>th</sup>, OR WHICH ARE DISTURBED AFTER OCTOBER 16<sup>th</sup>, SHALL BE STABILIZED WITH STONE OR EROSING CONTROL BLAIKERS APPROPRIATE FOR THE DESIGN FLOW COINDITION.
- AFTER OCTOBER 15™, INCOMPLETE ROAD OR PARKING SURFACES SHALL BE PROTECTED WITH A MINIMUM OF 3-INCHES OF CRUSHED GRAVEL PER NHOOT ITEM 304.3.

#### **CONSTRUCTION SEQUENCE:**

- CLEAR SITE ACCORDING TO PLAN.
- CONSTRUCTION OF TEUPORARY SEGMENT AND EROSION CONTROL MEASURES, TO BE IN ACCORDANCE WITH THE PLANS. PERIMETER CONTROLS TO BE INSTALLED PRIOR TO EARTH MOVING OPERATIONS.
- GRUB SITE ACCORDING TO PLAN
- CUT AND DISPOSE OF ANY DEBRIS PRODUCED DURING THE CLEARING AND GRUBBING ACTIVITY.
- CONSTRUCT DETERTION BASINS AND SWALES PRIOR TO ROUGH GRADING IN EACH PHASE. SEED AND MULCH IMMEDIATELY. SITE GRADING OF BUILDING AND PARKING AREAS. ALL CUT AND FILL SLOPES SHALL BE SEEDED AND MULCHED AFTER BEING CONSTRUCTED.
- AS THE RUILDING IS COMPLETED. ALL DISTURBED AREAS SHALL BE PERMANENTLY STABILIZED. NO PORTION OF THE PROJECT SHALL BE LEFT DISTURBED AND UNSTABILIZED FOR A PERIOD OF 41 DAYS OR GREATER. ALL DISTURBED AREAS SHALL BE PERMANENTLY STABILIZED PRIOR TO WINITER CONDITIONS TO STABILIZATION SHALL BE DEPRING A 570% VEGETATIVE GROWING BY NOVEMBER 157 OR INSTALLATION OF EROSION CONTROL MATTING.
- COMPLETED AREAS SHALL BE STABILIZED 72 HOURS AFTER COMPLETION
- ALL PERMANENT STORM WATER MANAGEMENT MEASURES SHALL HAVE A HEALTHY STAND OF VEGETATION ESTABLISHED PRIOR TO DIRECTING RUNOFF INTO THEM
- LOAM AND SEED ALL DISTURBED AREAS
- INSPECTION OF ALL SEDIMENT AND EROSION CONTROL MEASURES.
- SITE LANDSCAPING ALONG WITH PERMANENT SEEDING OF ALL DISTURBED AREAS
- REMOVE ANY TEMPORARY EROSION CONTROL MEASURES NOT NEEDED.

#### SITE MAINTENANCE/INSPECTION PROGRAM

THE FOLLOWING PROVIDES AN ITEM/ZATION OF SPECIFIC STIFE MAINTENANCE PRACTICES THAT VIII. LE EMPLOYED ON THE SITE TO MININZE POLIUTAINE ORBERATION AND TRAISFORT FROM IT ENTE. THE MAINTENANCE PROGRAM INCLUDES ROUTINE HISPECTIONS, PREVENTATIVE MAINTENANCE AND 'GOOD HOUSEKEEPING' PRACTICES.

#### **ROUTINE INSPECTIONS**

THE CONTRACTOR SHALL INSPECT ALL CONTROL MEASURES AT LEAST ONCE A WEEK AND WITHIN TWENTYFOUR 124 HOURS OF THE END OF A STORM WITH RAIRFALL AMOUNT GREATER THAN 0.5 INCHES. THE
INSPECTIONS WILL VERRIFT THAT THE STRUCTURAL BUPPA DESCRIBED IN THE PLANS ARE IN GOOD CONDTION
AND ARE MUNNIZING EROSION. A MAINTENANCE INSPECTION REPORT WILL BE MADE WITH EACH INSPECTION
COMPLETED INSPECTION FOR SHALL BE KEPT ON-SITE FOR THE OURATION OF THE PROJECT. FOLLOWING
CONSTRUCTION, THE COMPLETED FORMS SHALL BE RETAINED AT THE CONTRACTOR'S OFFICE FOR A MINIMUL
OF OHE YEAR.

#### PREVENTATIVE MAINTENANCE

THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTENANCE OF ALL TEMPORARY AND PERMANENT CONTROLS THROUGHOUT THE DURATION OF THIS CONTRACT. MAINTENANCE PRACTICES SHALL INCLUDE, BUT ARE NOT LIMITED TO.

- CLEANING OF CATCH BASINS TWICE PER YEAR OR MORE FREQUENTLY AS DICTATED BY QUARTERLY INSPECTIONS.
- CLEARING OF SEDMENT AND CEBRIS FROM STORMWATER MANAGEMENT AREA FOREBAY TWICE PER YEAR OR MORE FREQUENTLY AS DICTATED BY MONTHLY INSPECTIONS.
- 3. IMPLEMENTATION OF OTHER MAINTENANCE OR REPAIR ACTIVITIES AS DEEMED NECESSARY BASED UPON WEEKLY INSPECTIONS.
- REMOVAL OF BUILT UP SEDIMENT ALONG SILT FENCES AND/OR HAY BALE BARRIERS REMOVAL OF BUILT UP SEDIMENT IN BOTH TEMPORARY AND PERMANENT CONTROLS SUCH AS GRASS SWALES, SEDIMENT FOREBAYS AND RECHARGE/DETENTION BASINS.
- RECONSTRUCTING THE TEMPORARY GRAVEL CONSTRUCTION EXIT IF NOT WORKING PROPERLY RECURSI NUCLISIA THE TEMPORATY STAVEL CONTROLLED AS WATER FOOD WATER USE FLUENCE. TREATMENT OF HON-STORM WATER DISCHARGES SUCH AS WATER FROM WATER USE FLUENCE STORM WATER WAT
- 8. SWEEP PARKING LOTS AND DRIVES REGULARLY TO MINIMIZE SEDIMENT ACCUMULATION. FREQUENCY WILL VARY SEASOHALLY ACCORDING TO SEDIMENT ACCUMULATION ON PAVE SURFACES (E.G., MORE FREQUENT SWEEPING DURING THE WINTER AND SPRING).

#### GOOD HOUSEKEEPING PRACTICES

THE CONTRACTOR SHALL EMPLOY MEASURES AND PRACTICES TO REDUCE THE RISK OF SPILLS OR OTHER ACCIDENTAL EXPOSURE OF MATERIALS TO STORM AND WATER RUNGEF. THE CONTRACTOR SHALL PAY SPECIAL ATTENTION TO THE HANDLING, USE AND DISPOSAL OF MATERIALS SUCH AS PEROLEU. HE PRODUCTS IS REFINITIVE AND PARMED TO EXPONENT HIS THE PRODUCTS IS MINIMIZED. THE FOLLOWING GOOD HOUSEKEEPING "PRACTICES SHALL BE FOLLOWED DURING CONSTRUCTION OF THE PRODUCTS."

- A. AN EFFORT SHALL BE MADE TO STORE ONLY ENOUGH PRODUCT REQUIRED TO DO THE JOB.
- ALL MATERIALS STORED ON-SITE SHALL BE STORED IN A NEAT, ORDERLY MANNER IN THEIR APPROPRIATE CONTAINERS AND, IF POSSIBLE, UNDER A ROOF OR OTHER ENCLOSURE.
- C. PRODUCTS SHALL BE KEPT IN THEIR ORIGINAL CONTAINERS WITH THEIR MANUFACTURERS' LABELS
- WHENEVER POSSIBLE, ALL OF A PRODUCT SHALL BE USED BEFORE DISPOSING OF THE CONTAINER
   MANUFACTURERS' RECOMMENDATIONS FOR PROPER USE AND DISPOSAL SHALL BE FOLLOWED.
- THE CONTRACTOR SHALL INSPECT DAILY TO ENSURE PROPER USE AND DISPOSAL OF MATERIALS.

#### SPILL PREVENTION AND CLEANUP PRACTICES

- MANUFACTURERS' RECOMMENDED METHODS FOR SPILL CLEANUP WILL BE CLEARLY POSTED AND SITE PERSONNEL WILL BE MADE AWARE OF THE PROCEDURES AND THE LOCATION OF THE INFORMATION AND CLEANUP SUPPLIES
- MATERIALS AND EQUIPMENT HECESSARY FOR SPILL CLEANUP WILL BE KEPT IN THE MATERIAL STORAGE AREA ON-SITE EQUIPMENT AND MATERIAL MILL INCLUDE BUT HOT BE LIMITED TO BROOMS DUSTPAINS, MOOPS RAOS, GLOVES, GOGGLES, KITY LITTER, SAND, SAWDUST, AND PLASTIC AND METAL TRASH CONTAINERS SPECIFICALLY FOR THIS PURPOSE.
- ALL SPILLS WILL BE CLEARED UP IMMEDIATELY AFTER DISCOVERY
- THE SPILL AREA WILL BE KEPT WELL VENTILATED AND PERSONNEL WILL WEAR APPROPRIATE PROTECTIVE CLOTHING TO PREVENT INJURY FROM CONTACT WITH A HAZARDOUS SUBSTANCE.
- SPILLS OF TOXIC OR HAZARDOUS MATERIAL WILL BE REPORTED TO THE APPROPRIATE STATE OR LOCAL GOVERNMENT AGENCY, REGARDLESS OF THE SIZE.
- THE SPILL PREVENTION PLAN WILL BE ADJUSTED TO INCLUDE MEASURES TO PREVENT THIS TYPE OF SPILL FROM REOCCURRING AND HOW TO CLEAN UP THE SPILL IF THERE IS ANOTHER ONE. A DESCRIPTION OF THE SPILL IF AND THE SPILL IF THERE IS ANOTHER ONE. A DESCRIPTION OF THE SPILL WHAT CAUSED IT, AND THE CLEANUP MEASURES WILL ALSO BE INCLUDED.

9 THE CONTRACTOR SHAL FILE THE EPA NOTICE O INTENT (NOI) FORM AT LEAST 14 DAYS PRIOR TO CONSTRUCTION



MANUFACTURING ( HITCHINES 1 BUILDING ADMINISTRATION AIL ERET (MAP) HISH 

ON RUCTION

EV SOONS


Шē


2/17

COMPANT,

X


-6" Milli FLOW -






PROPOSED BUILDING

#### ACCESSIBLE PARKING DETAIL





CCEPTABLE SUBGRADE AS DETERMINED BY GEOTECHIRCAL ENGINEER 12" ITEM 304 3 CRUSHED GRAVE

4,000 PSI CONCRETE


• 4-1/2" SLUMP

• 5% TO 7% AIR ENTRAINED

- THE MAXIMUM ALLOWABLE SLOPE OF ACCESSIBLE ROUTE EXCLUDING CURB RAMPS SHALL BE 5%.
- THE MAXIMUM ALLOWABLE SLOPE OF ACCESSIBLE ROUTE CURB RAMPS SHALL BE 7.5%
- C CURB TREATMENT VANIES, SEE PLANS FOR CURB TREATMENT VANIES, SEE PLANS FOR CURB TREATMENT VANIES, SEE PLANS FOR CURB TREATMENT PONDING.

  SEE TYPICAL SIDEWALK SECTION FOR RAMP CONSTRUCTION.
- WHERE ACCESSIBLE ROUTES ARE LESS THAN 5 FT IN WIDTH (EXCLUDING CURB) A 5 FT x 5 FT PASSING
  AREA SHALL BE PROVIDED AT INTERVALS NOT TO EXCEED 200 FEET.
   ELIMINATE ALL CURBING AT RAINP (OTHER THAN VERTICAL CURBING, WHICH SHALL BE SET FLUSH)
  WHERE IT ABUTS PAVENERIT.

HANDICAP ACCESSIBLE **CURB RAMP DETAIL** 



TYP. PARKING STALL DETAIL

SECTION P2-10, P2-11

SECTION P-11 THRU P-16 
 LET/STH:
 P-11', 11'-0', P-12', 12'-0', P-14', 14'-0', P-16', 16'-0'

 WEIGHT PER LINEAR FOOT:
 3 00 LBS

 STEEL:
 SAME AS FOR P2-10', P2-11


 FIRISH:
 SAME AS FOR P2-10', P2-11

TRAFFIC SIGN SUPPORT DETAIL


**TYPICAL SECTION- PERMANENT** 


STONE CHECK DAM 'A'-'A'


SECTION P2-10, P2-11
LEIGHT: P2-10, 10-07, P2-11
LEIGHT: P2-10, 10-07, P2-11
LEIGHT: P2-10, 10-07, P2-11
LEIGHT: P2-10, 10-07, P2-11
LEIGHT: P3-10, 10-07, P2-11
LEIGHT: P3-10, P2-10, P2-11
LEIGHT: P3-10, P2-10, P2-11
LEIGHT: P3-10, P3-11
LEIGHT: P




**BOLLARD DETAIL** 







**CONCRETE SLAB DETAIL** 



P2-10, P2-11 P-11, P-12, P-14, P-16 POSTS

ACCEPTABLE SUBGRADE AS DETERMINED BY THE ENGINEER


**TYPICAL SECTION- PERMANENT** STONE CHECK DAM 'B'-'B'




COMPANT, 13055 (603) 673 HITCHINER MANUFACTURING 894 ELM STREET MILORD, NEW HAMPSHIRE O. BUILDING

NON INCIDION

REVIEW NOT FOR CONST





- NOTES:

  1. ALL MATERIALS AND INSTALLATION PROCEDURES WILL CONFORM TO TOWN OF MILFORD PUBLIC WORKS TECHNICAL SPECIFICATIONS.

  2. ALL PIPE SHOULD HAVE A MINIMAM DEPTH OF 5°0° FROM TOP OF PIPE TO FINSH GRADE.

  3. REQUIREMENTS FOR SUBSISE AND BUSE MATERIAL TYPE ARE TO BE IN ACCORDANCE WITH LOCAL AUTHORITY HAVING LOCAL JURISDICTION IN PAVED AREAS.

  4. REQUIREMENTS FOR GRAVEL, LOAM AIDDON SEED ARE TO BE IN ACCORDANCE WITH LOCAL AUTHORITY HAVING LOCAL JURISDICTION IN INCHAPAGE AREAS.
- 5. USE 10-GAUGE SOLID-CORE COATED BLUE TRACER WARE PER TOWN OF MILFORD PUBLIC WORKS TECHNICAL SPECIFICATIONS.

#### **TYPICAL TRENCH DETAIL**

UNIDISTLIRBED EARTH 4 MIL POLY BETWEEN CONCRETE AND FITTING IF POURED THRUST BLOCK MIN 2-2:47 PRE CAST
CONCRETE THRUST BLOCK
CONCRETE THRUST BLOCK
MIN FORD PUBLIC WORKS
APPROVAL OR CONCRETE
THRUST BLOCK POURED
AGAINST UNIXOSTURBED
BARTH - SUZE TO BE BASED
ON SIZE OF ITTIM OAND
PRESSURE IN WATER MAIN MEGALUG FOR DIPCL GRIP RING FOR PVC

- INV 1 ED.;

  ALL MATERIAL AND INSTALLATION PROCEDURES WILL CONFORM TO TOWN OF MILFORD PUBLIC WORKS TECHNOCAL SPECIFICATIONS.

  ALL PIPE SHOULD HAVE A MINIMUM DEPTH 5°4" FROM TOP OF PIPE TO FINISH GRADE.

  3. WYDS S. RODS SHALL BE USED IN CONJUNKTION WITH REQUIRED S.S. RATS. RODS ARE TO BE ATTACHED TO FITTINGS WITH HITHER STAR BOLTS OR DUE LUSS. TO PITTING OR SHALLER = (2) 3YD S.S. RODS & ASSICE. HARDWARE.

  12" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  14" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  14" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  15" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE. HARDWARE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE.


  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE.

  16" FITTING OR LANGER = (4) 3YD S.S. RODS & ASSICE.

  16" FITTING OR LANGER = (4) 3YD

#### TYPICAL THRUST BLOCK BEHIND FITTINGS INSTALLATION

STORM DRAIN / WATER MAIN




#### NOTES:

- ALL MATERIAL AND INSTALLATION PROCEDURES WILL CONFORM TO TOWN OF MILFORD PUBLIC WORKS TECHNOLIC, SPECIFICATIONS.

  ALL PIPE SHOULD HAVE A MIMIMUM DEPTHOF OF FROM TOP OF PIPE TO FINISH GRADE.

  3. 349 S & RODS SHALL BE USED IN CONJUNCTION WITH REQUIRED S S. INJTS. RODS ARE TO BE ATTACED TO FITTINGS WITH ETHER STAYS BOLTS ON DUC LIGIS.
- TO BE AT TACKED OF IN THE (3) 34" IS S. RODS & A SSCO. HARDWARE, 12" FITTING OR TO FITTING OR SIMULER (6) 34" IS S. RODS & A SSCO. HARDWARE, 12" FITTING OR LARGER (4) 34" IS S. RODS & A SSCO. HARDWARE, MIN 22" AND PER CAST CONCRETE THRUST BLOCK POWER OF ANY BLOCK POWER OF THE THRUST BLOCK POWER OF THE THRUST BLOCK POWER DAY BLOCK POWER OF THE THRUST BLOCK POWER DAY BLOCK POWER


#### TYPICAL TEE INSTALLATION ON EXISTING MAIN




#### NOTES:

- THE LENGTH OR WIDTH OF INSULATION SHALL EXTEND 1 STORM DRAIN PIPE DIAMETER BEYOND THE EDGE OF STORM DRAIN PIPE IN EACH DIRECTION OR MINIMUM OF 2 BEYOND THE CENTERLINE OF THE STORM DRAIN PIPE, WHICHE
- ALL BUTT JOINT SEAMS TO BE OVERLAPPED WITH A 1'-0' PIECE OF INSULATION CENTERED OVER SEAM.

#### INTERSECTION RUNS - ELEV. VIEW





#### TAPPING SLEEVE DETAIL


#### **WATER NOTES:** REFERENCE TOWN OF MILFORD PUBLIC WORKS SPECIFICATIONS FOR INSTALLATION OF ALL WATER LINES. 2. ALL SPRINKLER AND DOMESTIC LEADS TO BUILDING SHALL END 5-0" OUTSIDE THE FACE OF BUILDING WALL, UNLESS KOTED, AND SHALL BE PROVIDED WITH A TEMPORARY PLUG AT END (FOR OTHERS TO REMOVE AND EXTERN DAS INCESSARY). 3. THRUST BLOCKS AND MEGALUG RESTRAINTS SHALL BE PROVIDED AT ALL HORIZONTAL BEIND, TEES, AND PIRE HYDRAINTS. SEE DETAIL.

- MINIMUM COVER ON ALL WATER LINES IS 5'-0". CONTRACTOR SHALL MAINTAIN A 5-0" HORIZONTAL (URLESS OTHERWISE NOTED) AND 12" VERTICAL SEPARATION BETWEEN WATER SERVICE AND UTILITIES OTHER THAN SANTARY SEWER.
- SEWER

  INSPECTIONS ON WATER SERVICE INSTALLATION DURING CONSTRUCTION IS THE RESPONSIBILITY OF THE SITE CONTRACTOR AND SHALL BE COORDINATED WITH TOWN OF MILFORD PUBLIC WORKS, AND ALL INSPECTION FEES SHALL BE AND BY THE CONTRACTOR.

  CONTRACTOR SHALL HAVE BACTERIOLOGICAL AND PRESSURE TESTING PERFORMED. CONTRACTOR SHALL HAVE BACTERIOLOGICAL AND PRESSURE TESTING PERFORMED. CONTRACTOR SHALL MAYE BACTERIOLOGICAL AND PRESSURE TESTING PERFORMED. CONTRACTOR SHALL MAYE BACTERIOLOGICAL AND PRESSURE TESTING PERFORMED. CONTRACTOR SHALL BE OFFISTED TOWNINGS A COPY OF RESULTS. TOWN OF MILFORD PUBLIC WORKS SHALL BE OFFISTED TOWNINGS TEST.
- ALL PIPE, VALVES, MISCELLANEOUS MATERIALS AND INSTALLATION SHALL CONFORM WITH TOWN OF MILFORD PUBLIC WORKS SPECIFICATIONS. 9. ALL FIRE HYDRAITS, VALVES, FITTINGS, PIPES, ETC. SHALL BE IN ACCORDANCE WITH TOWN OF MILFORD PUBLIC WORKS REQUIREMENTS.
- OF MEPORD PUBLIC WORKS REQUIREMENTS.

  10. METALLIC TAPE OR DETECTOR WHISE SHALL BE INSTALLED IN THE SAME TRENCH WITH ALL NO METALLIC PAPE SUCH THAT THE PIPE MAY SE LOCATED WITH ELECTRONIC LOCATING EQUIPMENT, DETECTOR WINE OR METALLIC TAPE SHALL BE INSTALLED APPROXIMATELY 12 OADIES SOUND COPPER SUMPLEX BYXXXXI. OR EQUIAL METALLIC TAPE SHALL BE 2' MINIMUM METALLICED TAPE, GRIFFOLYN COMPANY, INC. TERRATAPE OR EQUIA.
- CONTRACTOR SHALL ENSURE ALL WATER VALVES ARE IN A FULLY-OPEN POSITION UPON COMPLETION OF PROJECT.
- 12. CONTRACTOR SHALL COORDINATE ALL WATER INTERRUPTIONS WITH THE TOWN OF MILFORD PUBLIC WORKS AND AFFECTED PROPERTY OWNERS



- A LL MATERIAL AHD INSTALLATION PROCEDURES WILL CONFORM TO TOWN OF MILFORD PUBLIC WORKS TECHNICAL SPECIFICATIONS.

  ALL INPESSHOULD HAVE A MIRIMAN DEPTHS OF 5' FROM TOP OF PIPE TO FINISH GRADE.

  34'0 S S. RODS SHALL BE USED IN CONJUNCTION WITH REQUIRED S S. INTIS. RODS ARE TO BE ATTACHED TO FITTINGS WITH CHITEMS TAYS BOLTS OF DUC LUGS. TO FITTING OR SMALLER \* (2) 34'0 S S. RODS A ASSOC, HARDWARE. 12' FITTING OR LARGER \* (4) 34'0 S S. RODS A ASSOC, HARDWARE.
- SATOR S. NOUS & ASSICE, PARKWARE.

  WHEN DESTRUCE FROM WATER MAIN TO HYDRANT IS MORE THAN 10' SUBSTITUTE

  MEGALUGS (OR GRIP RINGS) IN LIEU OF THREADED ROOS.

  MILY 22/27 FRE CAST CONCRETE THAND IS BLOCK MAY BE USED WITH TOMH OF MILFORD

  PUBLIC WORKS APPROVAL OR CONCRETE THANDS BLOCK POURED AGAINST

  LUCISTURBED EARTH-. SEE TO DE BLASED ON SIZE OF FITTING AND PRESSURE IN

  WATER MAIN. SEE THRUST BLOCK DETAIL.


TYPICAL HYDRANT INSTALLATION



SUCTION S REVIEW NOT FOR CONST  $\mathcal{M}$ COMPANT, MANUFACTURING HITCHINER A

BUILDING

M¥ M¥



#### General Specifications

- The contractor shall at their expense furnish all the materials, supplies, machinery, equipment, tool, superintendent, labor, insurance, & other accessories and services necessary to complete the said project within the unit costs stated within the bid price.
- The work to be done under this contract is as shown and described on the drawings. Each bidder shall make a careful examination of the plans and specifications ( the plan shall dictate quantities) and acquaint himself with all conditions before making their proposal. They will be held responsible for errors in their proposal resulting from their failure to make such an examination. All bidders shall visit the site and inform the
- The bids shall be based on materials and equipment complying with the drawings and the specifications. The contractor shall be responsible under this contract price, for furnishing and installing materials, confirming to the bid items. Under no circumstances may a species 'hybrid' be substituted or size changed without written consent of the landscape architect.
- The contractor shall be responsible for the protection of such existing utilities as water mains, sewer systems, gas mains, electrical conduits, telephone lines and any other utilities and if any damage or destruction may occur to these utilities, they shall be responsible for their repair and/or replacement at their
- The contractor shall make payment for all damages to buildings, structures, trees, shrubs and/or any other property outside the construction area or located within those limits but not designated for removal or reconstructed providing such damage shall result from accident caused by negligence for which the contractor shall be legally liable.
- 6. If additional labor and/or materials is requested or required, the contractor shall submit a price to the owner. If the owner approves the price they shall prepare a change order for approval and signature. The contractor shall not proceed without a written authorization from the owner for the additional work. If the contractor proceeds with the additional work without this authorization he shall forfeit any claim for additional compensation.
- The landscape architect (L.A.) shall reserve the right to inspect the project work at any time deemed necessary to Insure that the specifications and plans and any other contract documents are being followed.
- The L.A. shall have the right to reject any plant on-site based upon condition size, or incorrect species or hybrid. L.A. must be contacted prior to install, to inspect materials delivered to the site, and to insure that soil amendments, bark mulch, roof ballust, etc. are to the written specifications.
- All seeded areas shall receive a minimum 6" topsoil blanket (by site contractor) w/site preparation, raking and general clean up prior to application. Operatio shall include a preemergence type herbicide, 12 -25 -12 granular fertilizer @ 10 lbs./1000 sf., and pelletized limestone @ 25 1bs. /1000 s/f power raked into the top 2" of soil prior to hydro-seeding. Ratios & application rates may change based upon the required soil analysis.
- 10. Contractor is responsible for establishing a thick, weed free lawn. Seed shall be spread @ 4lbs./1000. Lawn germination shall be 95% free of noxious weeds for acceptance. Define differences in seed mixes (if applicable) with irrigation flagging until 2nd mowing. Site review by L.A. is required.

- 11. Review of the installed irrigation system by the designer is required prior to release of final payment
- 12. Hydroseeding operations shall be a one part process with a paper fiber mulch; a tackifier shall be applied on all slopes greater than 3:1, Excelsor Drainage mat shall be applied to all 2:1 slopes and drainage swales per plan.
- 13. Contractor shall maintain, from acceptance date, the lawn areas through the first mowing. Contractor is not responsible for the first mowing.
- 14. All plant materials shall be installed in accordance with A.L.C.C. Trees and shrubs shall have appropriate soil mixtures, fertilizer and soil retention granules.
- 15. If the soil conditions are extremely sandy, all trees shall have a 6" layer of compacted topsoil (verify with L.A.) placed in the base of the plant plt as a moisture retention laver. The plant pit sidewalls shall be over excavated by an additional 12" beyond the normal outside radius of the hole. A topsoil planting mixture shall be used to backfill as per spec # 22.
- 16. Landscape architect shall have the right to reject and have ground removed any plant material not of proper size or of weak quality, ie, thin, no lower branching, etc. Contractor must submit shipping lists (billing invoices) for verification, prior to installation.
- 17. All plant material shall be guaranteed for a period of one (1) year from date of installation. Any material which dies or does not show a healthy appearance within this time shall be replaced at the contractors expense; with same warranty requirements as the original. Warranty does not cover loss du mechanical damage, le, snow storage. Contractor should protect susceptible species from Insect Infestation. Use a liquid systemic application on birch, etc.
- 18. Plant beds and saucers vary in dia. (refer to dwg). Trees and shrubs shall receive a 4" (settled) covering of pine/hemlock bark mulch; saucer diameters per drawing & details. Deciduous trees shall have a 6' dia. saucer (typ.), evergreen trees shall have a saucer 2' min, beyond it's outer branches. All edges shall have a 'V' groove
- 19. All B&B material which are encased in wire baskets shall have the wires cut loose and the top third removed prior to backfill operation
- 20. If road base is encountered in any plant bed areas, ie. parking islands, it shall be removed and suitable amended soil installed per drawings and
- 21. Soll planting mixture shall be a 6%-10% organic topsoil, amended with 10% wood ash, 10%%% manure, & 30%%% peatmoss or incorporate a dehydrated compost material. If planting in sand, gravel or other well drained soils, a 50% peatmoss to excavated soil. Other soil amendments shall include: Agriform tablets, Hydro-Gel or equal, and Roots growth enhancer to all trees and shrubs listed, per manufacturers specifications. All plant material pits will receive a min. 20%%% in volume mix of a compost soll amendment. Submittal require 'Roots' STEP 1 can be substituted for the individual supplements. Install per
- 22. Landscape contractor shall not be responsible for topsoil spreading but shall coordinate with the site contractor adherence to the mound grades, plant bed soil depths and soil type per dwgs & spec. Landscape contractor shall power

- 23. Landscape contractor shall provide a soil analysis of the topsoil planting mixture. Analysis to show soil classification (min. sandy loam) and nutrients.
- 24. Contractor shall protect all B&B materials left above grade prior to installation from drying out. All plants shall be stored, covered in mulch, and irrigated until planted. Any plant left on the ground and whose outer ball surface drys out, shall be rejected by the landscape architect. Plants stored in shade and off
- 25. Plan dictates, contractor shall alert Landscape Architect if any discrepancies exist between the plan, the material list, and as-built site conditions
- 26. Installer shall notify landscape architect prior to planting, to review plant locations and bedline configurations. If contractor installs without the placement approval of the L.A., said architect shall have the right to relocate any installed plants at the contractor's expense.
- 27. Installer shall notify landscape architect prior to plant installation to review all materials. Any plants of poor condition, Improper size, or species will be
- 28. Upon one year review, contractor shall straighten any trees that have shifted Any weak or bare spots in lawn shall be reseeded
- 29. All bedlines shall have a deep 'V' groove to define lawn to mulch edge. No 'Beehive" mounding of mulch is allowed, also keep mulch away from base of
- 30. Do not plant materials too close to the edge of bedlines. Refer to drawings for center of plant to bedline. At a minimum no outer branching of a shrub or perennial shall be closer than two feet from the bedlines. If the as-built does not comply contractor shall adjust the plant location or bedline at his expense.
- 31. Seed mixes include: Sandy Soil Lawn Mix by: deercreekseed.com; New England Wetland Plants, Amherst, Ma, refer to planting plan for designations.
- 32. Any items not completed to the specifications will be required at contractors expense prior to final approvals. Contractor is to bid the work according to the specifications and not to what they may do under their standard practices Special attention will be payed to soils, amendments, guy stakes, bedline & saucer configurations, seed mixtures, etc.
- 33. Certain designated foundation edging is rood ballust (washed rounds, non-crushed, natural) Size of stone is a range of 3/4"-1.5"dia. placed to a depth of 3", upon placement apply a coating of granular Preen (preemergen
- Any questions concerning this drawing shall be directed to Joseph Hochrein, 85 Frost Lane, Webster, NH 03303, 603-648-2541,

#### MATERIAL BID LIST

	70 - 10 - 10 - 10 - 10 - 10 - 10 - 10 -	
1/ACE	ACER GRISEUM (PAPERBARK MAPLE)	8'-10'MULTI-STEM
13/BET	BETULA NIGRA (HERITAGE RIVER BIRCH)	10'-12' MULTI-STEP
27/DES	DESCHAMPSIA CESPITOSA (GOLDTAU TUFTED HAIR GRASS)	#2GAL.
10/HYD	HYDRANGEA QUERCIFOLIA (MUNCHKIN OAKLEAF HYDRANGEA)	#3GAL.
19.7.JAL	MALUS SPECIES (GOLD HARVEST CRABAPPLE)	2"-2.5"CAL.
8MPS	MALUS SPECIES (PINK SPIRES CRABAPPLE)	2"-2.5"CAL.
27/MIC	MICROBIOTA DECUSSATA (RUSSIAN CYPRESS)	#5GAL.
1/OXY	OXYDENORUM ARBOREUM (SOURWOOD)	2.5°-3"CAL.
1/TAX	TAXUS MEDIA (HICK'S YEW)	6'-7'BB
9/TEX	THUJA PLICATA EXCELSA (EXCELSA WESTERN ARBORVITAE	7'-888
6/RHD	RHODODENDRON SPECIES (CHIONOIDES RHODODENDRON)	#7GAL.
5/ТНО	THUJA PLICATA (WESTERN GREEN GIANT ARBOTVITAE)	8'-10'88
1/VIR	VIBURALIA REDON CHEDO VIBURALIA	2 61 2:00

#### MISCELLANEOUS:

NEW STONEWLL TO MATCH EXISTING (F.F. DETERMINED IN THE FIELD).

LAWN SEED TO MATCH SITE

BARK MILCH BEDS AND SAUCERS TO MATCH SITE

REMOVE ALL DEAD OR WEAK LIMBS, IN LARGE CALIPER TREES ALONG WILTON ROAL

REMOVE ALL UNDERSTORY ALONG THE WILTON ROAD STONE HEDGEROW

LOAM AND SEED AREA ALONG WILTON BOAD TO THE STONE HEDGEROW

#### GENERAL NOTES: 1 MATERIAL SOURCE, CATALOG REFERENCE: MILLICAYS NURSERY, CHICHESTER, N.H.

PLANT HYBRIO SUBSTITUTIONS OR PLANT SIZE IS NOT PERMITTED WITHOUT PRIOR WRITTEN CONSENT OF THE LANDSCAPE WICHTECT. ANY INSTALLED MATERIALS NOT CONFORMING TO THE BID LIST, SHALL BE REPLACED AT CONTRACTOR'S EPENSE.

ON PROCESSION


**>**SNO


COMPANT,

MANUFACTURING


HITCHINER 1


- 3 LANDSCAPE CONTRACTOR SHALL BE RESPONSIBLE FOR THE CARE OF PLANT MATERIALS FOR A ONE YEAR WARRANTY, PLANTS SHALL BE PROTECTED FROM DISEASE AND/OR INSECT INFESTATION.
- 4. DO NOT CREATE BEEHIVE SAUCERS AROUND TREES (DETRIMENTAL TO THE HEALTH OF PLANT MATERIAL
- 5 SHRUB BEDS ARE INTENDED TO CREATE A FULL COVER OF THE BED SURFACE, DO NOT SHEAR OR CLIP SHRUBS, DURING ANNUAL MAINTENANCE, ALL MATERIALS ARE TO GROW INTO ONE ANOTHER AS ONE MASS.














33,100 SF 6,990 SF

16,890 SF


56,980 SF

PHASE 1: FIRST FLOOR SECOND FLOOR

PHASE 2 FIRST FLOOR

TOTAL

OFFICE OPEN TO BELOW OPEN TO BELOW OPEN TO BELOW














A 08 A.0

(D) OVERALL EAST ELEVATION


SCALE: 1/16" = 1'-0"



52, (5) PHASE 1 | PHASE 2 -- TOP OF STEEL 126 - 3 1/2" - LEVEL 2 FOADING DOCK O OVERALL NORTH ELEVATION

SCALE: 1/16" = 1'-0"







# HITCHINER MANUFACTURING 194 ELM STREET, MILFORD, NH 03055

PROJECT:	<b>T</b> &
Date	Issue Description
	IDGELILLA KALDY DOLCALC
04/17/23 10/16/23	UPDATED PRICING GUP
32/23/24	GUP
<b></b>	
<b></b>	
<b> </b>	
<b></b>	ļ
<b></b>	
<b></b>	ļ
<b></b>	
<b>—</b>	
<b></b>	~~~~~~
<b>-</b>	
	1
<b></b>	
<del> </del>	
.05 74	SERVICTOR SERVICE
Architect	PROFESSIONAL SEA
Drawn By:	SFV
Project No.:	302216
Copyright	2023 PROCONILC.
Drawing Shee	
EXTE	KIOK

**ELEVATIONS** 

A3.01